

TECNICAL SPECIFICATION

		STANDARTS	SPECIFICATIONS
Surface treatment (UV)			Yes
Underlay		IXPE	1 mm
Total thickness		ISO24337	5 mm
Wear layer thickness		EN429	0.3 mm
Total weight		EN ISO 23997	8.0 kgs/sqm
Dimensional stability		TS EN ISO 23999	Class 34
Performance classification		23 . 34 . 43	
Residual indentation after static load		TS EN ISO 24343-1:2007	0.01 mm
Anti-slip resistance		EN 13893	DS
Electrostatic behavior		1815:2016	Anti static floor covering
Floor heating system		Suitable	Max.27 ⁰
Antibacterial		ISO 22196	Antibacterial
Pet-friendly			Pass
Phthalate analysis		Inhouse Methot	Phatalete free
Formaldehyde emissions		EN 717-1:2004	E1
Fire behavior		EN13501-1 EN 9239-1:2010	BFL-S1
Reaction to fire		EN 11925-2:2020	Bs-d0
Thermal resistance		EN 12667	0.296 W(m.K)
Matte Degree			2-4 ⁰
VOC emissions		FloorScore CE	Certified
Impact Sound Transmission		ASTM E492-09:2016 - ASTM E989-18	IIC=75dB
Airborne sound transmission loss		ASTM E413-16	Rw+C=75dB - STC = 73dB

