

1 Preparation of subfloor. Topboard and baseboard are shown. Dimensions: 22 3/64", 31 7/64", 56 cm, 79 cm. Thicknesses: 2 mm, 5/64", 4 mm, 5/32", 6 mm, 15/64".

2 Unifloor Dual product box. Icons: 24h, 45%-65% humidity, 18°C, and a crossed-out floor icon.

3 Vacuuming the subfloor. Humidity requirements: RH < 75%, sand cement screed 2%, wooden floor 10%, anhydrite 0.5%.

4 Checking floor flatness. A 1-meter straightedge is used. Maximum deviation: 3', max. 3 mm, 1/8".

5 Applying Unifloor PE-foil (150 µm, 4 mil) and Unifloor alutape. Dimensions: 1 15/16", 50 mm, 12", 200 mm.

6 Preparing the baseboard area.

7 Preparing the baseboard.

8 Laying the baseboard.

9 Installing the side strip. Dimensions: 15/64", 6 mm.

10 Laying the baseboard. Dimensions: 31 7/64", 79 cm, 28 cm, 11 1/32".

11 Laying the baseboard. Dimensions: 23 5/16", 59 cm, 31 7/64", 79 cm, 7 51/64", 20 cm, 28 cm, 11 1/32".

12 Laying the baseboard. Dimensions: 23 5/16", 59 cm, 31 7/64", 79 cm, 7 51/64", 20 cm, 56 cm, 22 3/64".

13 Laying the topboard. Dimensions: 28 x 59, 28 x 79, 56 x 79, 56 x 59, 56 x 79, 56 x 79. Thicknesses: 31 7/64", 23 5/16", 22 3/64", 11 1/32", 7 51/64", 79 cm, 59 cm, 56 cm, 28 cm, 20 cm.

14 Laying the topboard. Dimensions: 31 7/64", 79 cm, 15 35/64", 39.5 cm, 39.5 cm, 22 3/64", 56 cm, 56 cm.

15 Laying the topboard. Dimensions: 31 7/64", 22 3/64", 79 cm, 56 cm. Note: Follow sequence!

16 Sanding the topboard. Note: 120 grain sand paper.

17 Expansion joints. Dimensions: 33', max. 10 m, 15/32", min. 12 mm.

18 Expansion joints between rooms. Dimension: 15/32", min. 12 mm.

19 Final preparation. Icons: 48h, and a crossed-out floor icon. Dimensions: 15/64", 6 mm.

Unifloor Underlay Systems
Arnsbergstraat 4
7418 EZ Deventer - The Netherlands
T +31 (0) 570 85 55 33
E info@unifloor.nl

UK Toll Free 0845 603 0 906

**Service-Line für Deutschland,
Österreich & Schweiz:**
T +49 (152) 264 111 11

Marathon[®] DUAL

- ◆ Fast track floor prep system
- ◆ For Cushion Vinyl and Click LVT
- ◆ Levels out the substrate
- ◆ Creates a super smooth surface
- ◆ Perfectly stable
- ◆ Warmer feel on concrete
- ◆ High impact noise reduction
- ◆ Eco friendly

Marathon[®]
DUAL

Marathon[®]
PREMIUM

Marathon[®]
SUPER

FITTING INSTRUCTION FILM



uniFloor
UNDERLAY SYSTEMS BV

Unifloor Underlay Systems
Arnsbergstraat 4
7418 EZ Deventer - The Netherlands
T +31 (0) 570 85 55 33
E info@unifloor.nl

UK Toll Free 0845 603 0 906

Service-Line für Deutschland,
Österreich & Schweiz:
T +49 (152) 264 111 11

www.unifloor.nl